

## “PONTE” wooden bench with backrest “L” between “TIMELESS 1220” planters

Sheet code: **PACL005**

Drawing code: **AP34010202**

Revision: **22/01/2019**

**Designer:**  
Bellitalia Design Department



**Product:** Linear bench model “A PONTE” with backrest between “TIMELESS 1220” planters. The planters are equipped with a **levelling system** and a **water reserve system** to guarantee the soil the proper humidity level, avoiding the dispersion of internal water.

**Dimensions:** length: 4018 mm;  
width: 1220 mm;  
height: 850 mm;  
total weight: 1880 kg;  
capacity: 300 + 300 litres.

**Material:** The bench is composed by a seat and a backrest, respectively made of five and four wooden slats offered with three different types of essence: pine, okumè or exotic wood (please see respective material sheet). The slats are cut at their extremities to fit the lateral planters' perimeter and to be embedded in the two rings. The planters can be manufactured using reconstituted natural marble stones, white granite or grey concrete conglomerate. Copper or stainless steel central band.

**Reinforcing:** The seat's slats are linked with two thread bars M14, blocked with brass bolts and separated by pipes in black PVC. The thread bars are screwed to two brass supports that link the seat to the backrest. These supports are composed by two bended and internally threaded pipes. The planters' bases are reinforced and endowed with hooks that permit its lifting. The superior rings are also equipped with a circular reinforcement and steel stirrups with lifting hooks for the installation.

**Finishing:** The planters' surface can be polished, to give the product a shiny effect, otherwise sandblasted or bush-hammered, for a rough appearance. Surfaces are then covered with a transparent anti-decay coating, or, upon request, with anti-graffiti products. The copper band is painted with a protective coating for a durable shiny appearance, while the stainless steel band undergoes a satin finish treatment. All wooden elements in pine and okumè can be impregnated and painted with a protective varnish, the exotic wood is impregnated and, upon request, varnished. All edges are rounded or made blunt.

**Handling:** Use appropriate equipment when handling.

**Installation:** Place and level the two planters, leaving enough room to place the bench in a second moment. Bring the planters closer to obtain two lateral supporting slots.

